

# UNICO L2 basic

ceiling

090-1L243FBB01



Project / Type	
Notes	
Count / Date	



### General

Ceiling , Surface	
black , RAL 9005 <sup>1</sup>	
Reflector black	
IP20	
1050 lm	

### LED

2700 K	
CRI ≥ 90	
L90 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R <sub>g</sub> : 101 , R <sub>f</sub> : 91 , R <sub>f(1-15)</sub> : 89	
MR 0.56	
MDER 0.51	

### Optical

flood square	
beam angle 56°	
UGR < 19	
PstLM ≤ 1.0 <sup>2</sup>	
SVM ≤ 0.4 <sup>2</sup>	


### Electrical

DALI-2	
220-240 V	
system 12.6 W	
system 83 lm/W <sup>3</sup>	
PC1	

### Physical

length 88 mm	
width 51 mm	
height 90 mm	
0.35 kg	

### Light distribution



### Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

### Installation instructions



### Lighting calculator

