

STREAMCUT

surface

088-285151DA



Project / Type
Notes
Count / Date



General

Floor / Wall , Surface
tilt max 180°
dark grey
2710 lm
Beam Angle Correspondence Sphere (360°)
Non-directional light source
IP65
IK07
2710 lm
Chromaticity Coordinate X: 0.437
Chromaticity Coordinate Y: 0.411

LED

3000 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 97 , R _f : 91 , R _{1-15} : 89
MR 0.6
MDER 0.54

Optical

asymmetric

Electrical


non DIM
220-240 V
system 35 W
system 77 lm/W ¹
PC1

Physical


length 286 mm
width 135 mm
height 40 mm
1.9 kg

¹ FIXTURE: incl. consideration of optical losses & internal control unit losses
SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Light distribution



Product drawing



Installation instructions



STREAMCUT

surface

088-285151DA



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.94	0.91	0.88	0.85
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Mounting accessories

EARTH SPIKE

ARTICLE NUMBER(S)

088-2892110

