

STREAMCUT

surface

088-285151DA



Project / Type

Notes

Count / Date



220-240V

IP65

General

Floor / Wall , Surface

tilt max 180°

dark grey

2710 lm

Beam Angle Correspondence Sphere (360°)

Non-directional light source

IP65

IK07

2710 lm

Chromaticity Coordinate X: 0.437

Chromaticity Coordinate Y: 0.411

LED

3000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 97 , R_f: 91 , R_{1-15}: 89

MR 0.6

MDER 0.54

Optical

asymmetric

Electrical

non DIM

system 35 W

PC1 220-240V

system 77 lm/W¹

Physical

length 286 mm

width 135 mm

height 40 mm

1.9 kg


¹ incl. optical losses and the efficiency of the operating device (converter)

Installation instructions



Luminaire in aluminium in a simple, minimalist design; lamp head with integrated cooling fins; anodised surface and dark grey powder coated; suitable as surface mounted lights (wall, floor) can be swivelled plus/minus 90° and lockable every 30°; partially printed safety glass, fixed with stainless steel screws; incl. high quality lens system; asymmetric radiation characteristic; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP65; with pressure equalisation valve; PC1 220-240V; shock resistance IK07; ambient temperatures from -20°C to + 50°C; separate luminaire wiring compartment, suitable for through wiring; optional mounting screwed on or with ground spike (available as an accessory); accessories are listed separately; incl. converter, non dimmable;

Light distribution



Product drawing

