

STREAMCUT

wall
088-283151D



Project / Type


Notes

Count / Date




Recessed wall light in aluminium in a simple, minimalist design; anodised surface and dark grey powder coated; partially printed safety glass, fixed with stainless steel screws; reflector in matt anodised aluminium with asymmetric radiation characteristic; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP65; with pressure equalisation valve; PC1; 220-240 V; shock resistance IK08; ambient temperatures from -20°C to + 50°C; separate luminaire wiring compartment, suitable for through wiring; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Wall , Recessed

dark grey , RAL 9007 ¹

IP65

IK08

293 lm

LED

3000 K

CRI ≥ 80

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.56

MDER 0.51

Optical

asymmetric

Electrical

non DIM

220-240 V

system 8.4 W

system 35 lm/W²

PC1

Physical

length 150 mm

width 70 mm

height 200 mm

1.3 kg

Cutout

length 188 mm

width 140 mm

recessed depth 70 mm

¹ RAL code
² incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

