

# UNICO L2basic

ceiling

090-1L253DW001



Project / Type	
Notes	
Count / Date	



### General

Ceiling , Surface	
white , RAL 9016 <sup>1</sup>	
Reflector chrome	
IP20	
1090 lm	

### LED

3000 K	
CRI ≥ 90	
L90 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R <sub>g</sub> : 100 , R <sub>f</sub> : 92 , R <sub>f(1-15)</sub> : 91	
MR 0.64	
MDER 0.58	

### Optical

wide flood round	
beam angle 72°	
≥65° <3000 cd/m <sup>2</sup>	
PstLM ≤ 1.0 <sup>2</sup>	
SVM ≤ 0.4 <sup>2</sup>	


### Electrical

DALI-2	
220-240 V	
system 12.6 W	
system 87 lm/W <sup>3</sup>	
PC1	


### Physical

length 88 mm	
width 51 mm	
height 90 mm	
0.35 kg	

### Light distribution



### Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

### Installation instructions



### Lighting calculator

