

# BETO circle 1600 direct

suspended

074-7404D37B



Project / Type	
Notes	
Count / Date	



## General

Ceiling , Suspended	
white , RAL9010 <sup>1</sup>	
Reflector dark chrome	
IP20	
8400 lm	

## LED

tunable white	
2700 K - 6500 K	
CRI ≥ 90	
L90 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R <sub>g</sub> : 101 , R <sub>f</sub> : 90 , R <sub>f1-15</sub> : 88	
MR 0.51	
MDER 0.46	

## Optical

Reflector	
symmetric	
UGR < 16 , ≥65° <1500 cd/m <sup>2</sup>	
PstLM ≤ 1.0 <sup>2</sup>	
SVM ≤ 0.4 <sup>2</sup>	

## Electrical


DALI-2 DT8	
94 W	
PC1 220-240V	
89 lm/W	
2 DALI Addr.	

## Physical


diameter 1569 mm	
height 42 mm	

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator



[‘074-7404D37B’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com