

BETO circle 800 direct

suspended

074-7403538B



Project / Type
Notes
Count / Date



220-240V	X-PERT	UGR ≤ 16	cd/m ² ≤ 1500	CRI ≥ 80	1ADDR	X-PERT
----------	--------	----------	--------------------------	----------	-------	--------

General

Ceiling , Suspended
black , RAL9005 ¹
Reflector dark chrome
IP20
4590 lm

LED

3000 K
CRI ≥ 80
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
MR 0.56
MDER 0.51

Optical

Reflector
symmetric
UGR < 16 , ≥ 65° < 1500 cd/m ²
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical


DALI-2
46 W
PC1 220-240V
100 lm/W
1 DALI Addr.

Physical


diameter 807 mm
height 42 mm
5.2 kg

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator



[074-7403538B] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

02.10.2024