

DESO rounded

suspended


074-3245637P



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

white , RAL9010 ¹

IP20

indirect 3330 lm

direct 4400 lm

total 7730 lm

LED

4000 K

CRI ≥ 80

L80 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.66

Optical

Microprismatic

UGR < 19

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Rectangular light fitting with rounded corners in aluminium; flat design; surface white powder coated; suspended luminaire with 1500mm cable suspension; with integrated tool-less suspension height adjustment; incl. feed (white); direct/indirect light distribution; side coupled light, directed up and down; light control via a specially made indirect diffuser; microprismatic PMMA cover; homogeneous illumination; same light density for all surface lights with the same components; UGR ≤ 19; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; canopy with 2 cable openings and plug-in terminal for through wiring; degree of protection IP20; PC2 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Electrical

DALI-2

64 W

PC2 220-240V

121 lm/W

1 DALI Addr.

Physical

cable 1500 mm

length 1480 mm


width 295 mm

height 15 mm


5.1 kg

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator

