

# HEX-O MODULE FLAT 1000


suspended group  
073-693720W



Project / Type


Notes

Count / Date



Hexagonal acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of 60% recycled PET; high quality visual and tactile surface, white; foreign fiber inclusions possible; pendant fitting with 1500mm cable suspension (1 cable); height adjustment without tools; suitable for group installation; including rear rail for alignment of the housings; can be combined with all HEX-O ceiling and TRIG-O ceiling luminaires and acoustic elements; accessories are listed separately;

## Product drawing



General

Ceiling , Suspended

white

Physical

cable 1500 mm (min. 500 mm)

length 1000 mm

width 866 mm

height 40 mm

7.5 kg

Acoustics

Alpha w ( $\alpha_w$ ) up to 0.5 <sup>1</sup>

SAC (sound absorption class) up to D <sup>1</sup>

NRC up to 0.7 <sup>1</sup>

SAA up to 0.69 <sup>1</sup>

<sup>1</sup> Alpha w, SAC, NRC, SAA refer to the best result of the entire product family

## Installation instructions



# HEX-O MODULE FLAT 1000

suspended group  
073-693720W



Project / Type

Notes

Count / Date

## Equivalent sound absorption area ( $A_{eq}$ )

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.06	0.17	0.45	0.67	0.84	0.72

## Sound absorption coefficient ( $\alpha_p$ )

