

HEX-O MODULE 1000

suspended group
073-693710X



Project / Type


Notes

Count / Date



Hexagonal acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; high quality visual and tactile surface, acoustic special colours; foreign fiber inclusions possible; pendant fitting with 1500mm cable suspension (1 cable); height adjustment without tools; suitable for group installation; including rear rail for alignment of the housings; can be combined with all HEX-O ceiling and TRIG-O ceiling luminaires and acoustic elements;

Product drawing



General

Ceiling , Suspended

acoustic special colours

Physical

cable 1500 mm (min. 500 mm)

length 1000 mm

width 866 mm

height 100 mm

7.6 kg

Acoustics

Alpha w (α_w) up to 0.9 ¹

SAC (sound absorption class) up to A ¹

NRC up to 0.85 ¹

SAA up to 0.88 ¹

¹ Acoustic data calculations based on HEX-O MODULE 750, cavity 1cm

Installation instructions



HEX-O MODULE 1000

suspended group
073-693710X



Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.27	0.54	0.91	0.97	0.86	0.97

Sound absorption coefficient (α_p)

