

HEX-O MODULE FLAT 1000

suspended single
073-692720X



Project / Type


Notes

Count / Date



Hexagonal acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of 60% recycled PET; high quality visual and tactile surface, acoustic special colours; foreign fiber inclusions possible; pendant fitting with 1500mm cable suspension (3 cables); height adjustment without tools; suitable for single installation;

Product drawing



General

Ceiling , Suspended

acoustic special colours

Physical

cable 1500 mm (min. 500 mm)

length 1000 mm

width 866 mm

height 40 mm

7.5 kg

Acoustics

Alpha w (α_w) up to 0.5 ¹

SAC (sound absorption class) up to D ¹

NRC up to 0.7 ¹

SAA up to 0.69 ¹

¹ Alpha w, SAC, NRC, SAA refer to the best result of the entire product family

Installation instructions



HEX-O MODULE FLAT 1000

suspended single
073-692720X



Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.06	0.17	0.45	0.67	0.84	0.72

Sound absorption coefficient (α_p)

