

# HEX-O MODULE 1000

suspended single  
073-692710L



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Suspended \_\_\_\_\_  
black \_\_\_\_\_

## Physical

cable 1500 mm (min. 500 mm) \_\_\_\_\_  
length 1000 mm \_\_\_\_\_  
width 866 mm \_\_\_\_\_  
height 100 mm \_\_\_\_\_  
7,6 kg \_\_\_\_\_

## Acoustics

Alpha w ( $\alpha_w$ ) up to 0.9 <sup>1</sup> \_\_\_\_\_  
SAC (sound absorption class) up to A <sup>1</sup> \_\_\_\_\_  
NRC up to 0.85 <sup>1</sup> \_\_\_\_\_  
SAA up to 0.88 <sup>1</sup> \_\_\_\_\_


<sup>1</sup> Alpha w, SAC, NRC, SAA refer to the best result of the entire product family

## Installation instructions



Hexagonal acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of 60% recycled PET; high quality visual and tactile surface, black; foreign fiber inclusions possible; pendant fitting with 1500mm cable suspension (3 cables); height adjustment without tools; suitable for single installation;

## Product drawing



# HEX-O MODULE 1000

suspended single  
073-692710L



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_

## Equivalent sound absorption area ( $A_{eq}$ )

| 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ |
|--------|--------|--------|---------|---------|---------|
| 0.27   | 0.54   | 0.91   | 0.97    | 0.86    | 0.97    |

## Sound absorption coefficient ( $a_p$ )

