

HEX-O MODULE 750

suspended single
073-692610G



Project / Type


Notes

Count / Date



Hexagonal acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of 60% recycled PET; high quality visual and tactile surface, felt grey; foreign fiber inclusions possible; pendant fitting with 1500mm cable suspension (3 cables); height adjustment without tools; suitable for single installation; sound absorbing HEX-O ABSORBER available as an accessory; accessories are listed separately;

Product drawing



General

Ceiling , Suspended

felt grey

Physical

cable 1500 mm (min. 500 mm)

length 750 mm

width 650 mm

height 100 mm

4.7 kg

Acoustics

Alpha w (α_w) up to 0.9 ¹

SAC (sound absorption class) up to A ¹

NRC up to 0.85 ¹

SAA up to 0.88 ¹

¹ Alpha w, SAC, NRC, SAA refer to the best result of the entire product family

Installation instructions



HEX-O MODULE 750

suspended single
073-692610G



Project / Type


Notes

Count / Date

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.17	0.33	0.57	0.6	0.53	0.6

Sound absorption coefficient (α_p)



Acoustic accessories

HEX-O ABSORBER 1000

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
marble grey	1000-866-237	073-691740D
felt grey	1000-866-237	073-691740G
black	1000-866-237	073-691740L
white	1000-866-237	073-691740W
acoustic special colours	1000-866-237	073-691740X

