

BETO linear direct / indirect
power
suspended system
074-6036538B



Project / Type _____

Notes _____

Count / Date _____



| |
|-------------------------------|
| General |
| Ceiling , Suspended |
| black , RAL 9005 ¹ |
| Reflector dark chrome |
| IP20 |
| indirect 3710 lm |
| direct 2270 lm |
| total 5980 lm |

| |
|--------------------------|
| LED |
| 3000 K |
| CRI ≥ 80 |
| L90 / 50000 h |
| initial MacAdam ≤ 3 SDCM |
| MR 0.56 |
| MDER 0.51 |


| |
|-----------------------------|
| Optical |
| Reflector |
| symmetric |
| UGR ≤ 10 , ≥65° <1500 cd/m² |

| |
|------------------------------|
| Electrical |
| DALI-2 |
| 220-240 V |
| system 51 W |
| system 117 lm/W ² |
| PC1 |
| 2 DALI Addr. |


| |
|-----------------|
| Physical |
| length 1700 mm |
| width 42 mm |
| height 42 mm |
| 2.6 kg |

Luminaire housing made of extruded aluminium profile; extremely slim design (only 42 x 42 mm) linear; converter integrated into luminaire housing; no visible screws; angular design; for lighting systems; surface black powder coated; for suspended mounting (1500 mm cable suspension as an accessory); with integrated toolless suspension height adjustment on the luminaire; spring clip attachment to the luminaire; extruded profile for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high gloss reflector with faceted design; Reflector dark chrome; UGR ≤ 10; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; direct/indirect illumination characteristic; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination, separately controllable; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code
² FIXTURE: incl. consideration of optical losses & internal control unit losses
SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator



BETO linear direct / indirect power

suspended system

074-6036538B



Project / Type

Notes

Count / Date

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF | 0.98 | 0.96 | 0.94 | 0.92 | 0.9 |
| LSF | 1 | 1 | 1 | 1 | 1 |
| MF | LMF × RSMF × LLMF × LSF | | RSMF ^a | Room Surface Maintenance Factor | |
| MF | Maintenance Factor | | LLMF | Lamp Lumens Maintenance Factor | |
| LMF ^a | Luminaire Maintenance Factor | | LSF | Lamp Survival Faktor | |

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10 | 15 |
| B13 | 20 |
| B16 | 25 |
| B20 | 31 |
| B25 | 39 |
| C10 | 26 |
| C13 | 33 |
| C16 | 42 |
| C20 | 52 |
| C25 | 65 |

MOUNTING

END CAPS

| COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|------------|------------|-------------------|
| pure white | 30-42-42 | 074-6090017 |
| jet black | 30-42-42 | 074-6090018 |



LINEAR CONNECTOR

| ARTICLE NUMBER(S) |
|-------------------|
| 074-6091120 |

CABLE SUSPENSION

| COLOUR | ARTICLE NUMBER(S) |
|--------|-------------------|
| chrome | 005-2152110 |



CANOPY / FEEDER CABLE

| TYPE | COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|-------------------------|------------|------------|-------------------|
| 5 x 1,5 mm ² | pure white | 90-90-22 | 005-2212417 |
| 5 x 1,5 mm ² | jet black | 90-90-22 | 005-2212418 |



THROUGH WIRE

| TYPE | ARTICLE NUMBER(S) |
|-------------------------------------|-------------------|
| 5 x 1,5 mm ² 10 pieces | 004-90005 |



CORNER CONNECTOR

| TYPE | COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|--|------------|------------|-------------------|
| 90° incl. through wire 5 x 1,5 mm ² | pure white | 250-250-42 | 074-6091217 |
| 90° incl. through wire 5 x 1,5 mm ² | jet black | 250-250-42 | 074-6091218 |



BETO linear direct / indirect
power
suspended system
074-6036538B



Project / Type

Notes

Count / Date

OPTICAL

BLIND COVER

| TYPE | COLOUR | ARTICLE NUMBER(S) |
|--------|---------------|-------------------|
| 250 mm | traffic white | 074-6099107 |
| 250 mm | jet black | 074-6099108 |
| 500 mm | traffic white | 074-6099117 |
| 500 mm | jet black | 074-6099118 |

