

HEX-O MODULE 1000


ceiling
073-691710D



Project / Type

Notes

Count / Date



Hexagonal acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; high quality visual and tactile surface, marble grey; foreign fiber inclusions possible; suitable for ceiling mounting; convenient quick mounting system without tools; suitable for single or group installation; can be combined with all HEX-O ceiling and TRIG-O ceiling luminaires and acoustic elements;

General

Ceiling , Surface

marble grey

Physical

length 1000 mm

width 866 mm

height 100 mm

7.6 kg

Acoustics

Alpha w (α_w) up to 0.9 ¹

SAC (sound absorption class) up to A ¹

NRC up to 0.85 ¹


SAA up to 0.88 ¹

¹ Acoustic data calculations based on HEX-O MODULE 750, cavity 1cm

Installation instructions



Product drawing



[073-691710D] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com