

BETO direct / indirect

free standing T-shape

074-6945517R



Project / Type

Notes

Count / Date



General

Floor , Standing

white , RAL 9010 ¹

Reflector chrome

IP20

indirect 5020 lm

direct 1790 lm

total 6810 lm

LED

3000 K

CRI \geq 80

L90 / 50000 h

initial MacAdam \leq 3 SDCM

MR 0.56

MDER 0.51

Optical

Reflector

asymmetric

UGR < 13

PstLM \leq 1.0 ²

SVM \leq 0.4 ²

Electrical

touch DIM on pole

220-240 V

system 51 W

system 134 lm/W³

PC1

Physical

T-shape

length 1055 mm

width 42 mm


height 2100 mm

11.3 kg


¹ RAL code ² Value of containing product at full load (undimmed)

³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Light distribution



Product drawing



Installation instructions



[074-6945517R] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

06.04.2025