

# HEX-O 750

suspended group  
073-6361538P



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



220-240V X-PERT UGR ≤ 19 cd/m² ≤ 3000 CRI ≥ 80 RAL 9005 1 ADDR. X-PERT

## General

Ceiling , Suspended  
black , RAL9005 <sup>1</sup>  
IP20  
4210 lm

## LED

3000 K  
CRI ≥ 80  
L90 / 50000 h  
photobio. safety RG 0 - no Risk  
initial MacAdam ≤ 3 SDCM  
MR 0.54  
MDER 0.49

## Optical

Microprismatic  
microprismatic  
UGR < 19 , ≥65° <3000 cd/m²  
PstLM ≤ 1.0 <sup>2</sup>  
SVM ≤ 0.4 <sup>2</sup>

## Electrical


DALI-2  
35 W  
PC1 220-240V  
120 lm/W  
1 DALI Addr.

## Physical


cable 1500 mm (min. 500 mm)  
length 750 mm  
width 650 mm  
height 100 mm  
10 kg

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator



# HEX-O 750

suspended group  
073-6361538P



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.93	0.91	0.9
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup> Room Surface Maintenance Factor		
MF	Maintenance Factor		LLMF Lamp Lumens Maintenance Factor		
LMF <sup>a</sup>	Luminaire Maintenance Factor		LSF Lamp Survival Faktor		

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	9
B13	13
B16	15
B20	18
C10	18
C13	26
C16	30
C20	36

## Electrical accessories

### CANOPY / FEEDER CABLE

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
5 x 1,5 mm <sup>2</sup>	pure white	135	005-2232417
5 x 1,5 mm <sup>2</sup>	jet black	135	005-2232418
5 x 1,5 mm <sup>2</sup>	special colours	135	005-223241X



## Acoustic accessories

### HEX-O ABSORBER 1000

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
marble grey	1000-866-237	073-691740D
felt grey	1000-866-237	073-691740G
black	1000-866-237	073-691740L
white	1000-866-237	073-691740W
acoustic special colours	1000-866-237	073-691740X

