

# VELA 600 direct

surface

073-115151XK



Project / Type

Notes

Count / Date



IP40	220-240V	X-PERT	UGR ≤ 19	cd/m² ≤ 3000	CRI ≥ 80	X-PERT
------	----------	--------	----------	--------------	----------	--------

## General

Ceiling / Wall , Surface  
special colours  
IP40  
4060 lm

## LED

3000 K  
CRI ≥ 80  
L90 / 50000 h  
photobio. safety RG 0 - no Risk  
initial MacAdam ≤ 3 SDCM  
MR 0.54  
MDER 0.49

## Optical

Microprismatic  
microprismatic  
UGR < 19 , ≥ 65° < 3000 cd/m²  
PstLM ≤ 1.0 <sup>1</sup>  
SVM ≤ 0.4 <sup>1</sup>

## Electrical


non DIM  
31 W  
PC1 220-240V  
131 lm/W

## Physical


diameter 600 mm  
height 92 mm  
5.4 kg

Round luminaire housing in aluminium, rolled profile, seamlessly welded; surface special colours powder coated; highly reflective coating for improved efficiency; suitable for wall or ceiling mounting; convenient quick mounting system without tools; microprismatic PMMA cover; completely homogeneous illumination; UGR ≤ 19; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; luminaire with 2 cable openings and plug-in terminal for through wiring; degree of protection IP40; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



<sup>1</sup> Value of containing product at full load (undimmed)

## Installation instructions

