

VELA 600 direct

suspended

073-12516370



Project / Type


Notes

Count / Date




Round luminaire housing in aluminium, rolled profile, seamlessly welded; surface white powder coated; highly reflective coating for improved efficiency; suspended luminaire with 1500mm cable suspension; with integrated tool-less suspension height adjustment; incl. feed (white); completely homogeneously illuminated, satinised PMMA cover; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; canopy with 2 cable openings and plug-in terminal for through wiring; degree of protection IP40; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



IP40

220-240V

X-PERT

CRI ≥ 80

DALI-2
1ADDR.

X-PERT

General

Ceiling, Suspended

white, RAL9010 ¹

IP40

4250 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.66

Optical

Opal

opal (lamberts)

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2

31 W

PC1 220-240V

137 lm/W

1 DALI Addr.

Physical

cable 1500 mm

diameter 600 mm

height 87 mm

5.4 kg

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

