


MOVE IN 32 round

trimless

063-8111417S 063-8811117 002-90743



Project / Type
Notes
Count / Date



General

Ceiling , Semi-Recessed
white , RAL 9016 ¹
IP20
754 lm
fixture 86 lm/W ²

LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R _g : 99 , R _r : 91 , R _{t(1-15)} : 89
MR 0.53
MDER 0.48

Optical

spot
beam angle 18°
PstLM ≤ 1.0 ³
SVM ≤ 0.4 ³

Electrical

DALI-2
220-240 V
system 11.6 W
fixture 8.7 W
36 Vf
250 mA
PC2
1 DALI Addr.


Physical

trimless
diameter 63 mm
height 92 mm
0.5 kg

Cutout

diameter 54 mm
min. ceiling thickness 9 mm
max. ceiling thickness 25 mm
recessed depth 110 mm


Light distribution



spot 18°

h (m)	E0° (lx)	ø (m)
1	5710	0.32
2	1430	0.63
3	630	0.95
4	360	1.27
5	230	1.58

Product drawing



¹ RAL code
² FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

