

# TASK S linear direct / indirect TW power


suspended system  
059-57D8037K



Project / Type \_\_\_\_\_


Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



Luminaire housing made of aluminium with rounded edges; extremely flat (only 15mm) and slim (only 180mm) design; modern shape in an elegant design for high demands; for continuous lighting systems; surface white powder coated; with integrated toolless suspension height adjustment on the luminaire; convenient quick mounting system without tools; direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination, separately controllable; microprismatic PMMA cover; completely homogeneous illumination; same light density for all surface lights with the same components;  $UGR \leq 19$ ; light colour direct light component: 3000 K; light colour indirect light component: tunable white diodes (2700-6500 K); binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 converter; sound absorbing accessories available; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## General

Ceiling , Suspended  
white , RAL9010 <sup>1</sup>  
IP20  
indirect 4140 lm  
direct 6220 lm  
total 10360 lm

## LED

3000 K  
CRI  $\geq 90$   
L90 / 50000 h  
photobio. safety RG 0 - no Risk  
initial MacAdam  $\leq 3$  SDCM  
 $R_g: 96, R_r: 90, R_{t-15}: 90$   
MR 0.61  
MDER 0.56

## Optical

Microprismatic  
microprismatic  
UGR  $< 19$   
 $P_{stLM} \leq 1.0^2$   
 $SVM \leq 0.4^2$

## Electrical

DALI-2  
92 W  
PC1 220-240V  
113 lm/W  
2 DALI Addr.

## Physical

length 2315 mm  
width 180 mm  
height 34 mm  
7 kg

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator



# TASK S linear direct / indirect TW power

suspended system  
059-57D8037K



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.97	0.95	0.93	0.92
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup>	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF <sup>a</sup>	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	12
B13	16
B16	20
B20	25
C10	20
C13	27
C16	34
C20	41



# TASK S linear direct / indirect TW power

suspended system

059-57D8037K



Project / Type

Notes

Count / Date

## Mounting accessories

### LINEAR CONNECTOR

TYPE	COLOUR	ARTICLE NUMBER(S)
mechanical & electrical	pure white	059-2792317
mechanical & electrical	jet black	059-2792318
mechanical	pure white	059-2792417
mechanical	jet black	059-2792418



### CORNER CONNECTOR

TYPE	COLOUR	ARTICLE NUMBER(S)
90°   mechanical & electrical	pure white	059-2792717
90°   mechanical & electrical	jet black	059-2792718
90°   mechanical	pure white	059-2792817
90°   mechanical	jet black	059-2792818



### LONG LINEAR CONNECTOR

TYPE	COLOUR	ARTICLE NUMBER(S)
L 800 mm   mechanical & electrical	pure white	059-2792327
L 800 mm   mechanical & electrical	jet black	059-2792328
L 1200 mm   mechanical & electrical	pure white	059-2792337
L 1200 mm   mechanical & electrical	jet black	059-2792338
L 1200 mm   mechanical & electrical cuttable	pure white	059-2792307
L 1200 mm   mechanical & electrical cuttable	jet black	059-2792308
L 2400 mm   mechanical & electrical cuttable	pure white	059-2792347
L 2400 mm   mechanical & electrical cuttable	jet black	059-2792348



### CABLE SUSPENSION

COLOUR	ARTICLE NUMBER(S)
pure white	059-2792127



### END PIECE

TYPE	COLOUR	ARTICLE NUMBER(S)
incl. cable suspension	pure white	059-2792117
incl. cable suspension	jet black	059-2792118



### POWER FEEDER

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
5 x 1,5 mm <sup>2</sup>	pure white	106-36-1500	059-2792217
5 x 1,5 mm <sup>2</sup>	jet black	106-36-1500	059-2792218



### MIDDLE POWER FEEDER

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
5 x 1,5 mm <sup>2</sup>	pure white	100-100-1500	059-2792517
5 x 1,5 mm <sup>2</sup>	jet black	100-100-1500	059-2792518

