

TASK ACOUSTIC 1200 square wide


suspended
059-579266D



Project / Type


Notes

Count / Date



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; square design; high quality visual and tactile surface, marble grey; colour may deviate; direct sound is absorbed by the front-mounted fleece, sound reflected from the ceiling/wall by an additional, rear-mounted fleece; this creates high acoustic performance; pendant fitting with 1500mm cable suspension; toolless suspension height adjustment of the acoustic element;

Product drawing



General

Ceiling , Suspended

marble grey

Physical

panel only

length 1155 mm

width 1180 mm

height 30 mm

2.4 kg

Acoustics

Alpha w (α_w) up to 0.95 ¹

SAC (sound absorption class) up to A ¹

NRC up to 0.95 ¹

SAA up to 0.91 ¹

¹ Acoustic data calculations based on TASK ACOUSTIC 1200 half square, cavity 20cm

Installation instructions



TASK ACOUSTIC 1200 square wide

suspended
059-579266D



Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.75	1.02	1.56	1.94	2.24	2.45

Sound absorption coefficient (α_p)

