

TASK ACOUSTIC 1200 round


suspended
059-579236L



Project / Type


Notes

Count / Date



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of 50% recycled PET; round design; high quality visual and tactile surface, black; colour may deviate; direct sound is absorbed by the front-mounted fleece, sound reflected from the ceiling/wall by an additional, rear-mounted fleece; this creates high acoustic performance; pendant fitting with 1500mm cable suspension; toolless suspension height adjustment of the acoustic element;

Product drawing



General

Ceiling , Suspended

black

Physical

panel only

diameter 1155 mm

height 30 mm

4.2 kg

Acoustics

Alpha w (α_w) up to 0.95 ¹

SAC (sound absorption class) up to A ¹

NRC up to 0.95 ¹

SAA up to 0.91 ¹

¹ Alpha w, SAC, NRC, SAA refer to the best result of the entire product family

Installation instructions



TASK

ACOUSTIC 1200

round

suspended

059-579236L



Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.6	0.77	1.23	1.53	1.8	1.87

Sound absorption coefficient (α_p)

