

TASK

ACOUSTIC 600

round

suspended

059-579234X



Project / Type

Notes

Count / Date



General
Ceiling , Suspended
acoustic special colours
Physical
panel only
diameter 600 mm
height 30 mm
1.2 kg
Acoustics
Alpha w (α _w) up to 0.95 ¹
SAC (sound absorption class) up to A ¹
NRC up to 0.95 ¹
SAA up to 0.91 ¹


¹ Acoustic data calculations based on TASK ACOUSTIC 1200 half square, cavity 20cm

Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; round design; high quality visual and tactile surface, acoustic special colours; colour may deviate; direct sound is absorbed by the front-mounted fleece, sound reflected from the ceiling/wall by an additional, rear-mounted fleece; this creates high acoustic performance; pendant fitting with 1500mm cable suspension; toolless suspension height adjustment of the acoustic element;

Product drawing



TASK

ACOUSTIC 600

round

suspended

059-579234X



Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.21	0.22	0.36	0.43	0.49	0.53

Sound absorption coefficient (α_p)

