

TASK

ACOUSTIC 600

square

suspended

059-579214X



Project / Type

Notes

Count / Date



General
Ceiling , Suspended
acoustic special colours
Physical
panel only
length 600 mm
width 600 mm
height 30 mm
1.1 kg
Acoustics
Alpha w ( $\alpha_w$ ) up to 0.95 <sup>1</sup>
SAC (sound absorption class) up to A <sup>1</sup>
NRC up to 0.95 <sup>1</sup>
SAA up to 0.91 <sup>1</sup>


<sup>1</sup> Alpha w, SAC, NRC, SAA refer to the best result of the entire product family

Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of 50% recycled PET; square design; high quality visual and tactile surface, acoustic special colours; colour may deviate; direct sound is absorbed by the front-mounted fleece, sound reflected from the ceiling/wall by an additional, rear-mounted fleece; this creates high acoustic performance; pendant fitting with 1500mm cable suspension; toolless suspension height adjustment of the acoustic element;

Product drawing



TASK ACOUSTIC 600

square

suspended

059-579214X



Project / Type

Notes

Count / Date

Equivalent sound absorption area ( $A_{eq}$ )

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.2	0.27	0.41	0.51	0.59	0.65

Sound absorption coefficient ( $\alpha_p$ )

