

# TASK ACOUSTIC 600

## square

suspended

059-579214W



Project / Type

Notes

Count / Date



### General

Ceiling , Suspended  
white

### Physical

panel only  
length 600 mm  
width 600 mm  
height 30 mm  
1.1 kg

### Acoustics

Alpha w ( $\alpha_w$ ) up to 0.95<sup>1</sup>  
SAC (sound absorption class) up to A<sup>1</sup>  
NRC up to 0.95<sup>1</sup>  
SAA up to 0.91<sup>1</sup>


<sup>1</sup> Acoustic data calculations based on TASK ACOUSTIC 1200 half square, cavity 20cm

### Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; square design; high quality visual and tactile surface, white; colour may deviate; direct sound is absorbed by the front-mounted fleece, sound reflected from the ceiling/wall by an additional, rear-mounted fleece; this creates high acoustic performance; pendant fitting with 1500mm cable suspension; toolless suspension height adjustment of the acoustic element;

### Product drawing



# TASK ACOUSTIC 600

## square

suspended

059-579214W



Project / Type

Notes

Count / Date

### Equivalent sound absorption area ( $A_{eq}$ )

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.2	0.27	0.41	0.51	0.59	0.65

### Sound absorption coefficient ( $a_p$ )

