

TASK ACOUSTIC 1200 half round

surface


059-579146G



Project / Type

Notes

Count / Date



General

Ceiling, Surface

felt grey

Physical

panel only

length 1155 mm

width 573 mm

height 30 mm

3.9 kg

Acoustics

Alpha w (α_w) up to 0.6¹

SAC (sound absorption class) up to C¹

NRC up to 0.75¹

SAA up to 0.76¹


¹ Acoustic data calculations based on TASK ACOUSTIC 1200 half square, cavity 3cm

Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; half round design; high quality visual and tactile surface, felt grey; colour may deviate; direct sound is absorbed by the front-mounted fleece, sound reflected from the ceiling/wall by an additional, rear-mounted fleece; this creates high acoustic performance; for wall-/ceiling surface mounting;

Product drawing



TASK ACOUSTIC 1200 half round

surface

059-579146G



Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.03	0.16	0.37	0.53	0.53	0.53

Sound absorption coefficient (a_p)

