

SONIC direct / indirect

suspended

059-7421676P



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

dark grey , RAL7021¹

IP20

indirect 5230 lm

direct 5290 lm

total 10520 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.66

Optical

Microprismatic

microprismatic

UGR < 19

PstLM ≤ 1.0²

SVM ≤ 0.4²

Conical light housing in die-cast aluminium; surface dark grey powder coated; suspended luminaire with adjustable pendant rod mounting (chrome) 1000mm, feed in rod; direct/indirect illumination characteristic; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; indirect component covered with opal cover; direct lighting portion: micro prismatic PMMA cover; perfectly uniform illumination through use of a diffuse polycarbonate-based film; better light dispersion to transparency ratio; UGR ≤ 19; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; internal wiring in light halogen free; canopy with 2 cable openings and plug-in terminal for through wiring; luminaire with integrated infrared presence and brightness sensor (ESSENTIAL sensor); automatic light control for individually adjustable brightness; variable automatic shutdown; cable feed out to contact a push-button (230 VAC) to override the sensor; sound absorbing accessories available: acoustic elements made of high quality, self-supporting, recycled PET felt (high acoustic performance by doubling the material) or as an acoustically effective lampshade (large selection of colours) with sound absorbing properties; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Electrical

ESSENTIAL sensor (brightness & presence)

220-240 V

system 69 W

PC1

system 152 lm/W³

Physical

rod 1000 mm


diameter 500 mm

height 52 mm

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. optical losses and the efficiency of the operating device (converter)

Installation instructions



Lighting calculator





Project / Type _____

Notes _____

Count / Date _____

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.93	0.91	0.9
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	31
B13	40
B16	50
B20	62
B25	78
C10	52
C13	67
C16	85
C20	104
C25	130

Acoustic accessories

ABSORBER RING

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
white	1280	059-771111W
marble grey	1280	059-771111D
black	1280	059-771111L



SOUNDCAP

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
marble grey	527	059-773111D
felt grey	527	059-773111G
black	527	059-773111L
white	527	059-773111W
acoustic special colours	527	059-773111X

