

TASK

ACOUSTIC 600

round

surface

059-579134W



Project / Type

Notes

Count / Date



General

Ceiling , Surface

white

Physical

panel only

diameter 600 mm

height 30 mm

0.85 kg

Acoustics

Alpha w (α_w) up to 0.6 ¹

SAC (sound absorption class) up to C ¹

NRC up to 0.75 ¹

SAA up to 0.76 ¹


¹ Acoustic data calculations based on TASK ACOUSTIC 1200 half square, cavity 3cm

Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; round design; high quality visual and tactile surface, white; colour may deviate; direct sound is absorbed by the front-mounted fleece, sound reflected from the ceiling/wall by an additional, rear-mounted fleece; this creates high acoustic performance; for wall-/ceiling surface mounting;

Product drawing



TASK ACOUSTIC 600

round

surface

059-579134W



Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.01	0.08	0.2	0.28	0.28	0.28

Sound absorption coefficient (α_p)

