

# SONIC direct / indirect

suspended

059-7421576P



Project / Type

Notes

Count / Date



## General

Ceiling , Suspended

dark grey , RAL7021<sup>1</sup>

IP20

indirect 4940 lm

direct 5000 lm

total 9940 lm

## LED

3000 K

CRI  $\geq 80$

L90 / 50000 h

initial MacAdam  $\leq 3$  SDCM

MR 0.54

MDER 0.49

## Optical

Microprismatic

microprismatic

UGR  $< 19$

PstLM  $\leq 1.0$ <sup>2</sup>

SVM  $\leq 0.4$ <sup>2</sup>

## Electrical

ESSENTIAL sensor (brightness & presence)

220-240 V

system 69 W

PC1

system 144 lm/W<sup>3</sup>

## Physical


rod 1000 mm

diameter 500 mm


height 52 mm

Conical light housing in die-cast aluminium; surface dark grey powder coated; suspended luminaire with adjustable pendant rod mounting (chrome) 1000mm, feed in rod; direct/indirect illumination characteristic; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; indirect component covered with opal cover; direct lighting portion: micro prismatic PMMA cover; perfectly uniform illumination through use of a diffuse polycarbonate-based film; better light dispersion to transparency ratio; UGR  $\leq 19$ ; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 80$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; internal wiring in light halogen free; canopy with 2 cable openings and plug-in terminal for through wiring; luminaire with integrated infrared presence and brightness sensor (ESSENTIAL sensor); automatic light control for individually adjustable brightness; variable automatic shutdown; cable feed out to contact a push-button (230 VAC) to override the sensor; sound absorbing accessories available: acoustic elements made of high quality, self-supporting, recycled PET felt (high acoustic performance by doubling the material) or as an acoustically effective lampshade (large selection of colours) with sound absorbing properties; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)

## Installation instructions



## Lighting calculator

