

SONIC direct / indirect

suspended

059-7421536P



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

dark grey , RAL 7021 ¹

IP20

indirect 4940 lm

direct 5000 lm

total 9940 lm

LED

3000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.54

MDER 0.49

Optical

Microprismatic

microprismatic

UGR < 19

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2

220-240 V

system 69 W

system 144 lm/W³

PC1

1 DALI Addr.

Physical

rod 1000 mm


diameter 500 mm

height 52 mm


5.6 kg

Conical light housing in die-cast aluminium; surface dark grey powder coated; suspended luminaire with adjustable pendant rod mounting (chrome) 1000mm, feed in rod; direct/indirect illumination characteristic; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; indirect component covered with opal cover; direct lighting portion: micro prismatic PMMA cover; perfectly uniform illumination through use of a diffuse polycarbonate-based film; better light dispersion to transparency ratio; UGR ≤ 19; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; canopy with 2 cable openings and plug-in terminal for through wiring; incl. DALI-2 converter; sound absorbing accessories available: acoustic elements made of high quality, self-supporting, at least 50 % recycled PET felt (high acoustic performance by doubling the material) or as an acoustically effective lampshade (large selection of colours) with sound absorbing properties; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator

