

SONIC direct / indirect

suspended

059-722163XP



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

special colours

IP20

indirect 5230 lm

direct 5290 lm

total 10520 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.66

Optical

Microprismatic

microprismatic

UGR < 19

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Conical light housing in die-cast aluminium; surface special colours powder coated; suspended luminaire with 1500mm cable suspension; with integrated toolless suspension height adjustment on the luminaire; incl. feed (white); direct/indirect illumination characteristic; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; indirect component covered with opal cover; direct lighting portion: micro prismatic PMMA cover; perfectly unifrom illumination through use of a diffuse polycarbonate-based film; better light dispersion to transparency ratio; UGR ≤ 19; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; internal wiring in light halogen free; canopy with 2 cable openings and plug-in terminal for through wiring; incl. DALI-2 converter; sound absorbing accessories available: acoustic elements made of high quality, self-supporting, recycled PET felt (high acoustic performance by doubling the material) or as an acoustically effective lampshade (large selection of colours) with sound absorbing properties; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Electrical

DALI-2

220-240 V

system 69 W

PC1

system 152 lm/W²

1 DALI Addr.

Physical

cable 1500 mm (min. 500 mm)

diameter 500 mm


height 52 mm

5.5 kg

Light distribution



Product drawing



¹ Value of containing product at full load (undimmed)
² incl. optical losses and the efficiency of the operating device (converter)

Installation instructions



Lighting calculator

