

TASK

ACOUSTIC 600

square

surface


059-579114W



Project / Type

Notes

Count / Date



General

Ceiling , Surface

white

Physical

panel only

length 600 mm

width 600 mm

height 30 mm

1.9 kg

Acoustics

Alpha w ( $\alpha_w$ ) up to 0.6

SAC (sound absorption class) up to C

NRC up to 0.75

SAA up to 0.76


Acoustic data calculations based on TASK ACOUSTIC 1200 half square, cavity 3cm

Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; square design; high quality visual and tactile surface, white; colour may deviate; direct sound is absorbed by the front-mounted fleece, sound reflected from the ceiling/wall by an additional, rear-mounted fleece; this creates high acoustic performance; for wall-/ceiling surface mounting;

Product drawing



TASK ACOUSTIC 600

square

surface

059-579114W



Project / Type

Notes

Count / Date

Equivalent sound absorption area ( $A_{eq}$ )

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.02	0.11	0.25	0.36	0.36	0.36

Sound absorption coefficient ( $\alpha_p$ )

