

TASK S direct / indirect soft

suspended

059-525613XK



Project / Type	
Notes	
Count / Date	



General

Ceiling , Suspended	
special colours	
IP20	
indirect 521 lm	
direct 3040 lm	
total 3560 lm	

LED

4000 K	
CRI ≥ 90	
L90 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R _g : 96 , R _f : 90 , R ₍₁₋₁₅₎ : 87	
MR 0.75	
MDER 0.68	

Optical

Microprismatic	
microprismatic	
UGR < 19 , $\geq 65^\circ$ <3000 cd/m ²	
P _{st} LM ≤ 1.0 ¹	
SVM ≤ 0.4 ¹	

Electrical


DALI-2	
220-240 V	
system 29.2 W	
system 122 lm/W ²	
PC1	
1 DALI Addr.	

Physical


cable 1500 mm	
length 1748 mm	
width 180 mm	
height 34 mm	
5.1 kg	

¹ Value of containing product at full load (undimmed)
² FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Light distribution



Product drawing



Installation instructions



Lighting calculator

