

# LINEA opal / 1 spot

wall

058-6178D47BH



Project / Type

Notes

Count / Date



RG0  
IEC 62471

220-240V

X-PERT

X-PERT

## General

Wall , Surface

white , RAL9010 <sup>1</sup>

3350 lm/m

IP20

indirect 4030 lm

direct 4030 lm

total 8060 lm

tilt max 89°

141 lm

## LED

3000 K<sup>2</sup>-tunable white<sup>3</sup>

2700 K - 5000 K

CRI ≥ 90

L80 / 50000 h<sup>2</sup>-L85 / 50000 h<sup>3</sup>

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 100<sup>2</sup>-99<sup>3</sup>, R<sub>f</sub>: 91<sup>2</sup>-90<sup>3</sup>, R<sub>f(1-15)</sub>: 88

MR 0.59<sup>2</sup>-0.53<sup>3</sup>

MDER 0.53<sup>2</sup>-0.48<sup>3</sup>

## Optical

High Performance Opal

flood<sup>2</sup>-opal (Iambertsch)<sup>3</sup>

PstLM ≤ 1.0 <sup>4</sup>

SVM ≤ 0.4 <sup>4</sup>

beam angle 23°

## Electrical

DALI-2 / switch (only spotlights)<sup>2</sup>-DALI-2 DT8 / switch (only spotlights)<sup>3</sup>

2.2<sup>2</sup>-83<sup>3</sup> W

PC1 220-240V

64<sup>2</sup>-97<sup>3</sup> lm/W

1 DALI Addr.

35 W/m

## Physical

length 2510 mm


width 40 mm

height 100 mm

left

Light fitting and front cover made of extruded aluminium profile; angular design; no visible screws; surface white powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour: tunable white diodes (2700-5000 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; JUST 26 spotlight module 2,2 W / 141 lm / 3000 K left, incl. switch; incl. DALI-2 / DT8 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


## Light distribution



flood 23° Spot

h (m)	E0° (lx)	ø (m)
1	584	0.41
2	146	0.83
3	65	1.24
4	37	1.65
5	23	2.07

## Product drawing



<sup>1</sup> RAL code <sup>2</sup> Spot <sup>3</sup> Linear  
<sup>4</sup> Value of containing product at full load (undimmed)

## Installation instructions

