

# TASK direct / indirect soft

free standing T-shape  
059-2953056Z



Project / Type

Notes

Count / Date



General
Floor , Standing
grey , RAL 9006 <sup>1</sup>
IP20
indirect 3350 lm
direct 4100 lm
total 7450 lm

LED
3000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 96 , R <sub>f</sub> : 90 , R <sub>(1-15)</sub> : 90
MR 0.61
MDER 0.56


Optical
Microprismatic
microprismatic
UGR < 19
P <sub>stLM</sub> ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

Electrical
touch DIM on pole
220-240 V
system 71 W
system 105 lm/W <sup>3</sup>
PC1


Physical
T-shape
length 800 mm
width 320 mm
height 1920 mm
11.7 kg

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Light distribution



## Product drawing



## Installation instructions

