

LINEA opal / asymmetric

wall


058-6178517AA



Project / Type


Notes

Count / Date




Light fitting and front cover made of extruded aluminium profile; angular design; no visible screws; surface white powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct light component: HPO (High Performance Opal) cover for uniform illumination; indirect light component: with specially computed, asymmetrical lens for homogeneous lighting intensity (installation optionally for floor or ceiling illumination); light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Wall , Surface

white , RAL9010 ¹

3210 lm/m

IP20

indirect 4190 lm

direct 3520 lm

total 7710 lm

LED

3000 K

CRI ≥ 90

L85 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_f: 91 , R_{f(1-15)}: 89

MR 0.61

MDER 0.55

Optical

High Performance Opal / Asymmetric

asymmetric

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

non DIM

71 W

PC1 220-240V

109 lm/W

29 W/m

Physical

length 2410 mm

width 40 mm

height 100 mm

5.9 kg

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions

