

LINEA opal / 1 spot

wall

058-6174648CH



Project / Type

Notes

Count / Date



General

Wall , Surface

black , RAL 9005 ¹

IP20

indirect 1900 lm

direct 1940 lm

total 3840 lm

3190 lm/m

tilt max 89°

141 lm

LED

3000 K²-4000 K³

CRI ≥ 90

L80 / 50000 h²-L85 / 50000 h³

initial MacAdam ≤ 3 SDCM

R_g: 100²-98³, R_f: 91²-90³, R_{f(1-15)}: 88

MR 0.59²-0.76³

MDER 0.53²-0.69³

Optical

High Performance Opal

flood²-opal (lambertsch)³

PstLM ≤ 1.0^{3 2 4}

SVM ≤ 0.4^{3 2 4}

beam angle 23°

Electrical

DALI-2 / switch (only spotlights)

220-240 V

system 2.2²-35³ W

system 64²-110³ lm/W⁵

PC1

1 DALI Addr.

29 W/m

Physical

length 1310 mm

width 40 mm

height 100 mm

right


¹ RAL code ² Spot ³ Linear

⁴ Value of containing product at full load (undimmed)


⁵ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Light fitting and front cover made of extruded aluminium profile; angular design; no visible screws; surface black powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; JUST 26 spotlight module 2,2 W / 141 lm / 3000 K right, incl. switch; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



flood 23° Spot

h (m)	E0° (lx)	ø (m)
1	584	0.41
2	146	0.83
3	65	1.24
4	37	1.65
5	23	2.07

Installation instructions

