

LINEA opal / 2 spots

wall

058-6174638DH



Project / Type


Notes

Count / Date



Light fitting and front cover made of extruded aluminium profile; angular design; no visible screws; surface black powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97 ; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; 2x JUST 26 spotlight module 2,6 W / 159 lm / 3000 K (1x left, 1x right); incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



flood 30° Spot

h (m)	E0° (lx)	ø (m)
1	419	0.54
2	105	1.09
3	47	1.63
4	26	2.17
5	17	2.72

Product drawing



General

Wall , Surface
black , RAL 9005 ¹
IP20
indirect 1900 lm
direct 1940 lm
total 3840 lm
3190 lm/m
tilt max 89°
344 lm

LED

3000 K²-4000 K³
CRI $\geq 97^{2-90^3}$
L95 / 50000 h²-L85 / 50000 h³
initial MacAdam ≤ 3 SDCM
R_g: 92²-98³ , R_f: 86²-90³ , R_{f(1-5)}: 94²-88³
MR 0.53²-0.76³
MDER 0.48²-0.69³

Optical

High Performance Opal
flood²-opal (lambertsch)³
PstLM $\leq 1.0^{3-2-4}$
SVM $\leq 0.4^{3-2-4}$
beam angle 30°

Electrical

DALI-2
220-240 V
system 5.4²-35³ W
system 64²-110³ lm/W⁵
PC1
2²-1³ DALI Addr.
29 W/m

Physical

length 1410 mm
width 40 mm
height 100 mm

¹ RAL code ² Spot ³ Linear
⁴ Value of containing product at full load (undimmed)
⁵ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

