

# LINEA opal / opal

wall

058-6172638AH



Project / Type

Notes

Count / Date




Light fitting and front cover made of extruded aluminium profile; angular design; no visible screws; surface black powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/ indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour 4000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## General

Wall , Surface

black , RAL9005 <sup>1</sup>

3210 lm/m

IP20

indirect 972 lm

direct 972 lm

total 1944 lm

## LED

4000 K

CRI  $\geq 90$

L85 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 98 , R<sub>r</sub>: 90 , R<sub>t[1-15]</sub>: 88

MR 0.76

MDER 0.69

## Optical

High Performance Opal

opal (lambertsch)

P<sub>stLM</sub>  $\leq 1.0$  <sup>2</sup>

SVM  $\leq 0.4$  <sup>2</sup>

## Electrical

DALI-2

17.6 W

PC1 220-240V

110 lm/W

1 DALI Addr.

29 W/m

## Physical

length 610 mm

width 40 mm

height 100 mm

1.6 kg

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Installation instructions

