

LINEA opal / 1 spot

wall

058-6172548BH



Project / Type _____

Notes _____

Count / Date _____



General

Wall , Surface _____

black , RAL9005 ¹ _____

2890 lm/m _____

IP20 _____

indirect 873 lm _____

direct 873 lm _____

total 1746 lm _____

tilt max 89° _____

141 lm _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h²-L85 / 50000 h³ _____

photobio. safety RG 0 - no Risk _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89 _____

MR 0.61 _____

MDER 0.55 _____

Optical

High Performance Opal _____

PstLM ≤ 1.0 ⁴ _____

SVM ≤ 0.4 ⁴ _____

flood _____

beam angle 23° _____

Electrical

DALI-2 / switch (only spotlights) _____

2.2²-17.6³ W _____

PC1 220-240V _____

64²-99³ lm/W _____

1 DALI Addr. _____

29 W/m _____

Physical

length 710 mm _____

width 40 mm _____

height 100 mm _____


2.19 kg _____

left _____

¹ RAL code ² Spot ³ Linear


⁴ Value of containing product at full load (undimmed)

Light distribution



flood 23°		Spot
h (m)	E0° (lx)	ø (m)
1	584	0.41
2	146	0.83
3	65	1.24
4	37	1.65
5	23	2.07

Product drawing



Installation instructions

