

# LINEA opal / opal

wall

058-6171618AH



Project / Type

Notes

Count / Date



## General

Wall , Surface

black , RAL 9005 <sup>1</sup>

IP20

indirect 472 lm

direct 472 lm

total 944 lm

3100 lm/m

## LED

4000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 98 , R<sub>r</sub>: 90 , R<sub>t(1-5)</sub>: 88

MR 0.76

MDER 0.69

## Optical

High Performance Opal

opal (lambertsch)

P<sub>stLM</sub> ≤ 1.0<sup>2 3</sup>

SVM ≤ 0.4<sup>2 3</sup>

## Electrical

non DIM

220-240 V

system 9.7 W

system 97 lm/W<sup>4</sup>

PC1

32 W/m

## Physical

length 310 mm


width 40 mm

height 100 mm


1 kg

Light fitting and front cover made of extruded aluminium profile; angular design; no visible screws; surface black powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



<sup>1</sup> RAL code <sup>2</sup> Linear

<sup>3</sup> Value of containing product at full load (undimmed)

<sup>4</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Installation instructions

