

MIRA 200 round

trim

052-94245380



| |
|----------------|
| Project / Type |
| Notes |
| Count / Date |



General

| |
|------------------------------|
| Ceiling , Recessed |
| black , RAL9005 ¹ |
| IP20 |
| 4380 lm |

LED

| |
|--|
| 3000 K |
| CRI \geq 90 |
| L80 / 50000 h |
| initial MacAdam \leq 3 SDCM |
| R _g : 99 , R _f : 91 , R ₍₁₋₁₅₎ : 89 |
| MR 0.61 |
| MDER 0.55 |

Optical

| |
|-------------------------------|
| Opal |
| opal (lambertsch) |
| PstLM \leq 1.0 ² |
| SVM \leq 0.4 ² |

Electrical

| |
|-----------------------------|
| DALI-2 |
| no emergency light |
| system 50 W |
| PC2 220-240V |
| system 88 lm/W ³ |
| 1 DALI Addr. |


Physical

| |
|-----------------|
| trim |
| diameter 200 mm |
| height 53 mm |


Cutout

| |
|------------------------------|
| diameter 190 mm |
| min. ceiling thickness 2 mm |
| max. ceiling thickness 25 mm |
| recessed depth 90 mm |

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. optical losses and the efficiency of the operating device (converter)

Installation instructions



Lighting calculator

