

MINIMAL 100 high lumen

trimless

052-33M5637H



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| |
|------------------------------|
| Ceiling , Recessed |
| white , RAL9016 ¹ |
| 3000 lm/m |
| IP20 |
| 4420 lm |

LED

| |
|---------------------------------|
| 4000 K |
| CRI ≥ 80 |
| L90 / 50000 h |
| photobio. safety RG 0 - no Risk |
| initial MacAdam ≤ 3 SDCM |
| MR 0.72 |
| MDER 0.66 |

Optical

| |
|--------------------------|
| High Performance Opal |
| opal (lambertsch) |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Electrical

| |
|--------------|
| DALI-2 |
| 34 W |
| PC1 220-240V |
| 130 lm/W |
| 1 DALI Addr. |
| 23 W/m |

Physical


| |
|----------------|
| trimless |
| length 1476 mm |
| width 102 mm |
| height 82 mm |
| 5.1 kg |

Cutout


| |
|------------------------------|
| length 1479 mm |
| width 106 mm |
| min. ceiling thickness 8 mm |
| max. ceiling thickness 25 mm |
| recessed depth 106 mm |

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator

