

MINIMAL 100 high lumen

trimless

052-33M4537H



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Recessed _____

white , RAL9016 ¹ _____

2850 lm/m _____

IP20 _____

3340 lm _____

LED

3000 K _____

CRI ≥ 80 _____

L90 / 50000 h _____

photobio. safety RG 0 - no Risk _____

initial MacAdam ≤ 3 SDCM _____

MR 0.54 _____

MDER 0.49 _____

Optical

High Performance Opal _____

opal (lambertsch) _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

system 27.5 W _____

PC1 220-240V _____

system 121 lm/W³ _____

1 DALI Addr. _____

23 W/m _____

Physical

trimless _____

length 1176 mm _____

width 102 mm _____

height 82 mm _____

4.1 kg _____

Cutout

length 1179 mm _____

width 106 mm _____


min. ceiling thickness 8 mm _____

max. ceiling thickness 25 mm _____

recessed depth 106 mm _____

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. optical losses and the efficiency of the operating device (converter)

Light distribution



Product drawing

