

# SETA 60 CONEX reflector

## direct / indirect plug / socket

suspended system

058-4129637R



Project / Type

Notes

Count / Date



### General

Ceiling , Suspended

white , RAL 9010 <sup>1</sup>

chrome

IP20

indirect 9270 lm

direct 9030 lm

total 18300 lm

### LED

4000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.65

### Optical

Reflector

symmetric

UGR < 16 , ≥65° <1500 cd/m<sup>2</sup>

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

### Electrical

DALI-2

220-240 V

system 110 W

system 166 lm/W<sup>3</sup>

PC1

2 DALI Addr.

### Physical

length 2936 mm

width 60 mm


height 60 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

### Light distribution

### Product drawing



### Installation instructions



### Lighting calculator

