

# MOVE IT 25 S track corner

indirect

050-741103G



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

gold , gold dust/RAL9005 <sup>1</sup>

Inner colour black

15200 lm/m

IP20

1550 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.61

MDER 0.55

Electrical

DALI-2 single control

13.1 W

PC3 48V

118 lm/W

129 W/m

Physical

length 637 mm


width 610 mm

height 31 mm


1 kg

90° angle connector; Thin extruded aluminium profile with 31mm height and 28mm width groove; for suspended mounting (1500 mm cable suspension as an accessory); height adjustment without tools; with indirect light component for additional accentuation of the ceiling; indirect light component covered with opal lens cover; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with integrated power track profile for take off of supply voltage and DALI signal; surface gold; powder coated / anodised; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3 48V; accessories are listed separately; light source not replaceable;

Light distribution



Product drawing



<sup>1</sup> RAL code

Installation instructions



Lighting calculator

