


MOVE IT 25 S track corner

indirect

050-741101G



Project / Type	
Notes	
Count / Date	



General

Ceiling , Suspended
gold , gold dust/RAL9005 ¹
Inner colour black
15200 lm/m
IP20
1550 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 99 , R _f : 91 , R ₍₁₋₁₅₎ : 89
MR 0.61
MDER 0.55

Optical

P _{stLM} ≤ 1.0 ²
SVM ≤ 0.4 ²


Electrical

non DIM
48 V
inset 13.1 W
PC3
inset 118 lm/W ³
129 W/m


Physical

length 637 mm
width 610 mm
height 31 mm
1 kg

Light distribution



Product drawing



[050-741101G] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com