

MOVE IT 25 track corner indirect


050-740101X



Project / Type

Notes

Count / Date




90° angle connector; Extruded aluminium profile with 28mm width groove; for suspended mounting (1500 mm cable suspension as an accessory); height adjustment without tools; with indirect light component for additional accentuation of the ceiling; indirect light component covered with opal lens cover; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with integrated power rail profile for supply voltage feed; surface special colours powder coated; Inner colour anodised black; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3; 48 V; accessories are listed separately; light source not replaceable;

Light distribution



Product drawing



General

Ceiling , Suspended

special colours

Inner colour black

IP20

1550 lm

1730 lm/m

optical inset 70 lm/W¹

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89

MR 0.61

MDER 0.55

Electrical

non DIM

48 V

fixture 13.1 W

optical inset 11.2 W

PC3

15 W/m

Physical

length 637 mm

width 610 mm

height 60 mm

1.4 kg

¹ OPTICAL INSET: incl. consideration of optical losses

Installation instructions



Lighting calculator

