




Project / Type _____

Notes _____

Count / Date _____



General

Ceiling / Wall , Recessed
 white , RAL 9016 ¹
 front IP40 , back IP20
 1220 lm
 2000 lm/m

LED

3000 K
 CRI ≥ 80
 L90 / 50000 h
 initial MacAdam ≤ 3 SDCM
 MR 0.54
 MDER 0.49

Optical

High Performance Opal
 opal (lambertsch)
 PstLM ≤ 1.0 ²
 SVM ≤ 0.4 ²

Electrical

DALI-2
 220-240 V
 system 10.8 W
 system 113 lm/W³
 PC2
 1 DALI Addr.
 18 W/m

Physical


trimless
 length 616 mm
 width 92 mm
 height 13 mm
 1.6 kg

Cutout


length 619 mm
 width 95 mm
 min. ceiling thickness 12.5 mm
 max. ceiling thickness 25 mm
 recessed depth 58 mm
 recessed depth: 12.5 mm (ceiling) + 45 mm (converter)

Low profile recessed channel, height 13 mm; suitable for rimless installation in 12.5mm plasterboard ceilings; specially designed trim with grooves for better adhesion of smoothing compound; suitable for wall or ceiling mounting; surface white powder coated; easy mounting without need to cut the substructure; fall-safe light inset made of extruded aluminium profile, can be inserted in the canal without tools by magnetic holders; side coupled light directed downward through LGP (LIGHT GUIDING PRISM) body and high efficiency reflector; HPO (High Performance Opal) cover for uniform illumination; flush cover; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection from below IP40 (from above IP20); PC2; 220-240 V; internal wiring in light halogen free; incl. external converter for ceiling insertion; DALI-2 control; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions

